



- GENERAL NOTES:**
1. MEDIA NOT INCLUDED WITH FILTER
 2. CONCRETE SLAB TO BE DESIGNED BY OTHERS
 3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND RESINS
 4. FILTERS HAVE UV STABILIZED CLEAR COAT SCHEDULE 80 PVC
 5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF
 6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER. PLEASE SPECIFY AT TIME OF ORDER.
 7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.

FILTER DATA	
TOTAL SURFACE AREA:	39 SQ. FT.
MAX WORKING PRESSURE:	50 PSI.
MAX FLOW RATE:	20 GPM / SQ. FT.
MEDIA REQUIREMENTS	
SAND:	4,800 LBS
GRAVEL:	2,650 LBS
WEIGHTS	
FILTER SHIPPING WEIGHT:	1,144 LBS
FILTER OPERATING WEIGHT:	15,650 LBS



HORIZONTAL SAND FILTER (20901)
63"x91" WITH 6" 4 VALVE MANIFOLD

DRAWN BY:	MM	DWG. NO.:	20901-2	REV.:	
SCALE:	3/8" = 1'	DATE:	10/21/02	CHECKED:	