



6'-0<u>3</u>" [1848]

16" Ø MANWAY (SEE NOTES 6&7)

3/4" MANUAL . AIR PURGE

3'-11 76" [1204]

- GENERAL NOTES:

  1. MEDIA NOT INCLUDED WITH FILTER
  2. CONCRETE SLAB TO BE DESIGNED BY OTHERS
  3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND RESINS
  4. FILTERS HAVE UV STABILIZED CLEAR COAT
  5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 80 PVC.
  6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER, PLEASE SPECIFY AT TIME OF ORDER.
  7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.

FILTER DATA	
TOTAL SURFACE AREA:	39 SQ. FT.
MAX WORKING PRESSURE:	50 PSI.
MAX FLOW RATE:	20 GPM / SQ. FT.
MEDIA REQUIREMENTS	ITS
SAND:	4,800 LBS
GRAVEL:	2,650 LBS
WEIGHTS	

S		0				
SCALE: 3/8" = 1"		DRAWNBY:	63"x9	HORIZ		AS
DATE:	≥	M	)1" W	/TNC		
DATE: 10/21/02		DWG. NO: 20901	HORIZONTAL SAND FILTER (20901) 63"x91" WITH 6" CONNECTIONS	AL SAND FI	USA	ASTRAL POOL
CHECKED:	0901				00L	
			SNC	0901)		>
		RE				

FILTER OPERATING WEIGHT: FILTER SHIPPING WEIGHT

> 1,144 LBS 14,950 LBS