



- GENERAL NOTE:**
1. MEDIA NOT INCLUDED WITH FILTER
 2. CONCRETE SLAB TO BE DETERMINED BY OTHERS
 3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND RESIN
 4. FILTERS HAVE UV STABILIZED CLEAR COAT
 5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 80 PVC.
 6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER. PLEASE SPECIFY AT TIME OF ORDER.
 7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.

FILTER DATA

TOTAL SURFACE AREA:	92 SQ. FT.
MAX WORKING PRESSURE:	50 PSI.
MAX FLOW RATE:	20 GPM / SQ. FT.
MEDIA REQUIREMENTS	
SAND:	5,400 LBS EA
GRAVEL:	3,100 LBS EA
WEIGHTS	
FILTER SHIPPING WEIGHT:	1,365 LBS EA
FILTER OPERATING WEIGHT:	34,900 LBS



DUAL HORIZONTAL FILTER (20902)
63" X 106" W/ 8" 5 VALVE MANIFOLD

DRAWN BY: MM DWG NO: 20902-6 REV: _____
SCALE: 1/4" = 1' DATE: 10/30/02 CHECKED: _____